



SAFETY DATA SHEET

1. Identification

Product identifier LPS® Electro Contact Cleaner

Other means of identification
Part Number 00416

Recommended use A non-flammable solvent blend for the removal of dirt, moisture, dust, flux and oxides from the internal components of electronic or precision equipment such as circuit boards and the internal components of electronic devices used in factories and other industrial settings.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information
Manufacturer
Manufacturer

Company name ITW Pro Brands
Address 4647 Hugh Howell Rd.
Tucker, GA 30084
Country (U.S.A.)
Tel: +1 770-243-8800

In Case of Emergency 1-800-424-9300 (inside U.S.)
+001 703-527-3887 (outside U.S.)

Website www.lpslabs.com
E-mail lpssds@itwprobrands.com

2. Hazard(s) identification

Physical hazards Gases under pressure Liquefied gas

Health hazards Not classified.

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Contains gas under pressure; may explode if heated.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Protect from sunlight. Store in a well-ventilated place.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Ethane, 1,1,1,2-tetrafluoro-(hfc-134a)		811-97-2	40 - 50
Methyl Nonafluorobutyl ether		163702-07-6	10 - 20

Chemical name	Common name and synonyms	CAS number	%
Methyl Nonafluoroisobutyl ether		163702-08-7	10 - 20
Perfluoro Compounds, (Primarily compounds with 6 Carbons)		86508-42-1	10 - 20
1,2-trans-dichloroethylene		156-60-5	5 - 10
Cyclohexylmethane		108-87-2	1 - 5
Isopropanol		67-63-0	1 - 5

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	No specific first aid measures noted.
Ingestion	Not likely, due to the form of the product.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. ALWAYS stay away from tanks engulfed in flame. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Cool containers exposed to flames with water until well after the fire is out.
General fire hazards	Contents under pressure. Pressurized container may explode when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.
Methods and materials for containment and cleaning up	Isolate area until gas has dispersed. Stop the flow of material, if this is without risk. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 1 Aerosol. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS). Level 1 Aerosol.

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Cyclohexylmethane (CAS 108-87-2)	PEL	2000 mg/m3
Isopropanol (CAS 67-63-0)	PEL	500 ppm
		980 mg/m3
		400 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
1,2-trans-dichloroethylene (CAS 156-60-5)	TWA	200 ppm
Cyclohexylmethane (CAS 108-87-2)	TWA	400 ppm
Isopropanol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Cyclohexylmethane (CAS 108-87-2)	TWA	1600 mg/m3
		400 ppm
Isopropanol (CAS 67-63-0)	STEL	1225 mg/m3
		500 ppm
		980 mg/m3
	TWA	400 ppm

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value	Form
Ethane, 1,1,1,2-tetrafluoro-(hfc-134a) (CAS 811-97-2)	TWA	1000 ppm	8 hour
Methyl Nonafluorobutyl ether (CAS 163702-07-6)	TWA	750 ppm	
Methyl Nonafluoroisobutyl ether (CAS 163702-08-7)	TWA	750 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Isopropanol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear appropriate chemical resistant gloves.

Other

Wear suitable protective clothing.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Gas.

Form Aerosol.

Color Colorless.

Odor Characteristic.

Odor threshold Not established

pH Not applicable

Melting point/freezing point Not established

Initial boiling point and boiling range 118.4 °F (48 °C)

Flash point None (Tag-Closed Cup)

Evaporation rate < 1 (Ethyl Ether = 1)

Flammability (solid, gas) Non flammable gas.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not established

Flammability limit - upper (%) Not established

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 3103 mm Hg @ 20°C

Vapor density > 1

Relative density Not available.

Solubility(ies)

Solubility (water) < 5 % by weight

Partition coefficient (n-octanol/water) < 1

Auto-ignition temperature > 482 °F (> 250 °C)

Decomposition temperature Not established

Viscosity < 3 cSt @ 25°C

Other information

Explosive properties Not explosive.

Heat of combustion < 20 kJ/g

Oxidizing properties Not oxidizing.

Percent volatile 100 %

Specific gravity 1.38 - 1.4 @ 25°C

VOC 45 % per US State & Federal Consumer Product Regulations

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions Hazardous polymerization does not occur.

Conditions to avoid Heat. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products Combustion will generate smoke, possibly thick and choking, resulting in zero visibility and combustion products include hydrogen fluoride, hydrogen chloride, fluorine, chlorine, carbon monoxide and carbon dioxide.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
1,2-trans-dichloroethylene (CAS 156-60-5)		
Acute		
Oral		
LD50	Rat	1235 mg/kg
Cyclohexylmethane (CAS 108-87-2)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 6564 ppm, 1 Hours
Isopropanol (CAS 67-63-0)		
Acute		
Dermal		
LD50	Rabbit	16.4 ml/kg, 24 Hours
Oral		
LD50	Rat	4.7 g/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
ACGIH Carcinogens		
Isopropanol (CAS 67-63-0)	A4 Not classifiable as a human carcinogen.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Not listed.		
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)		
Not regulated.		
US. National Toxicology Program (NTP) Report on Carcinogens		
Not listed.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not likely, due to the form of the product.	

Chronic effects Prolonged inhalation may be harmful.

Further information None known.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Cyclohexylmethane (CAS 108-87-2)		
Aquatic		
Fish	LC50	Striped bass (<i>Morone saxatilis</i>)
		5.8 mg/l, 96 hours
Isopropanol (CAS 67-63-0)		
Aquatic		
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>)
		> 1400 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)	
1,2-trans-dichloroethylene	2.06
Cyclohexylmethane	3.61
Ethane, 1,1,1,2-tetrafluoro-(hfc-134a)	1.06
Isopropanol	0.05

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
D003: Waste Reactive material

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, non-flammable
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

IATA

UN number	UN1950
UN proper shipping name	Aerosols, non-flammable
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	No.

ERG Code 10L
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Other information

Passenger and cargo aircraft Allowed with restrictions.
Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1950
UN proper shipping name AEROSOLS
Transport hazard class(es)
Class 2.2
Subsidiary risk -
Packing group Not applicable.
Environmental hazards
Marine pollutant No.
EmS F-D, S-U
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

DOT



IATA; IMDG



General information Ensure compliance with applicable regulations.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

1,2-trans-dichloroethylene (CAS 156-60-5) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No
 Delayed Hazard - No
 Fire Hazard - No
 Pressure Hazard - Yes
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)
 Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Isopropanol (CAS 67-63-0)

Low priority

US state regulations

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,2-trans-dichloroethylene (CAS 156-60-5)

Isopropanol (CAS 67-63-0)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 12-27-2016
Version # 01

Disclaimer

ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information

This document has undergone significant changes and should be reviewed in its entirety.